

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

**Amendments to the Claims:**

Please cancel Claims 83 and 89 and amend Claims 16-21, 23-29, 38, 43, 51-53, 55-57, 60-61, 74, 94, 96, 98-105 as follows:

1. (original) A card cleaning device for use in an image forming machine, comprising:
  - (a) a housing adapted to be removably coupled to said image forming machine;
  - (b) a first cleaning member removably coupled to said housing and adapted to clean a card being fed at an angle relative to said housing, said housing being adapted to receive said card at an angle; and
  - (c) a second cleaning member removably coupled to said housing and adapted to clean said first cleaning member during machine operation.
2. (original) The card cleaning device of claim 1, wherein said second cleaning member is in frictional contact with said first cleaning member and adapted to clean said first cleaning member during machine operation.
3. (original) The card cleaning device of claim 1, wherein said first cleaning member includes a first roller having a shaft removably coupled to said housing and said second cleaning member includes a second roller having a core removably coupled to said housing, said second roller being in frictional contact with said first roller and adapted to clean said first roller during machine operation.
4. (original) The card cleaning device of claim 3, further comprising a lid rotatably coupled to said housing substantially over said second roller for rotating between an open position for roller maintenance and a closed position during machine operation, said lid adapted to contact said core of said second roller when said lid is in said closed position.
5. (original) The card cleaning device of claim 4, further comprising at least one spring operatively coupled between said lid and said housing for spring loading said lid, said spring-loaded lid exerting pressure on said core of said second roller when said lid is in said closed

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

position, said pressure being transferred to said first roller as a result of said frictional contact between said first and second rollers.

6. (original) The card cleaning device of claim 5, further comprising a first drive roller disposed substantially under said first roller and in frictional contact with a card being fed for passing said card under said first roller for card cleaning.

7. (original) The card cleaning device of claim 3, further comprising means for guiding the entry of a card being fed at an angle relative to said housing.

8. (original) The card cleaning device of claim 7, wherein said entry guiding means includes at least one card entry guide coupled to said housing substantially under said first roller for establishing a zone of first contact for said card and for preventing premature wear of said first roller during card feeding.

9. (original) A card cleaning system for use with an image forming machine, comprising:  
(a) a housing adapted to be removably coupled to said image forming machine;  
(b) a first cleaning member removably coupled to said housing and adapted to clean a card being fed at an angle relative to said housing along a card entry path, said housing being adapted to receive said card at an angle, said angle substantially defined between said card entry path and a card exit path relative to said housing;  
(c) means for feeding said card at an angle relative to said housing; and  
(d) a second cleaning member removably coupled to said housing and adapted to clean said first cleaning member during machine operation.

10. (original) The card cleaning system of claim 9, wherein said second cleaning member is in frictional contact with said first cleaning member and adapted to clean said first cleaning member during machine operation.

11. (original) The card cleaning system of claim 9, wherein said first cleaning member includes a first roller having a shaft removably coupled to said housing and said second cleaning

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

member includes a second roller having a core removably coupled to said housing, said second roller being in frictional contact with said first roller and adapted to clean said first roller during machine operation.

12. (original) The card cleaning device of claim 11, further comprising a lid rotatably coupled to said housing substantially over said second roller for rotating between an open position for roller maintenance and a closed position during machine operation, said lid adapted to contact said core of said second roller when said lid is in said closed position.

13. (original) The card cleaning device of claim 12, further comprising at least one spring operatively coupled between said lid and said housing for spring loading said lid, said spring-loaded lid exerting pressure on said core of said second roller when said lid is in said closed position, said pressure being transferred to said first roller as a result of said frictional contact between said first and second rollers.

14. (original) The card cleaning device of claim 13, further comprising a first drive roller disposed substantially under said first roller and in frictional contact with a card being fed for passing said card under said first roller for card cleaning.

15. (original) The card cleaning device of claim 11, wherein said card feeding means includes a card feeder disposed proximate to said housing substantially over said card entry path, a second drive roller disposed substantially under said card feeder for translating said card along said card entry path and at least one card entry guide coupled to said housing substantially under said first roller for establishing a zone of first contact for an entering card and for preventing premature wear of said first roller during card feeding, said card feeder mechanism adapted to bend said card upon card contact with said at least one card entry guide to enable card feeding at an angle relative to said housing.

16. (currently amended) For use in a printer or other system forming images on cards or other such media,  
a replaceable media cleaning cartridge comprising:

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

- a. a first cleaning component structured and arranged to engage and present to a moving media unit being cleaned, a changing first contact surface area; and
- b. a second cleaning component structured and arranged to engage and present to said first cleaning component, a changing second contact surface area, whereby to clean the first cleaning component;
- c. the tackiness of said second contact surface area being greater than the tackiness of said first contact surface areas which in turn is greater than the tackiness of a media unit such that said first contact surface area adhesively attracts particles from a media unit being cleaned, and said second contact surface area adhesively attracts particles from said first contact surface area.

17. (currently amended) The media cleaning cartridge of claim 16 wherein said first cleaning component comprises a roller.

18. (currently amended) The media cleaning cartridge of claim 16 wherein said second cleaning component comprises a roller.

19. (currently amended) The media cleaning cartridge of claim 16 wherein said second cleaning component is structured for quick removal from said cartridge.

20. (currently amended) The media cleaning cartridge of claim 16 wherein said first cleaning component is structured for quick removal from ~~fr~~ said cartridge.

21. (currently amended) The media cleaning cartridge of claim 16 wherein both of said first and second cleaning components are structured for quick removal from said cartridge.

22. (previously presented) The media cleaning cartridge of claim 16 wherein said second contact surface is replaceable.

23. (currently amended) The media cleaning cartridge of claim 16 wherein said cartridge has a frame which supports said first and second cleaning components, said frame being configured such that at least said first cleaning component is supported in a slot in said frame.

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

24. (currently amended) The media cleaning cartridge of claim 16 wherein said cartridge has a frame which supports said first and second cleaning components, said frame being configured such that at least said second cleaning component is supported in a slot in said frame.

25. (currently amended) The media cleaning cartridge of claim 16 wherein said cartridge has a frame which supports said first and second cleaning components, said frame being configured such that said first and second cleaning components are supported in one or more slots in said frame.

26. (currently amended) ~~The media cleaning cartridge of claim 16~~ For use in a printer or other system forming images on cards or other such media,

a replaceable media cleaning cartridge comprising:

a. a first cleaning component structured and arranged to engage and present to a moving media unit being cleaned, a changing first contact surface area; and

b. a second cleaning component structured and arranged to engage and present to said first cleaning component, a changing second contact surface area;

c. the tackiness of said second contact surface area being greater than the tackiness of said first contact surface areas which in turn is greater than the tackiness of a media unit such that said first contact surface area adhesively attracts particles from a media unit being cleaned, and said second contact surface area adhesively attracts particles from said first contact surface area, wherein said cartridge includes a resilient member adapted to bias said second cleaning component into engagement with said first cleaning component.

27. (currently amended) ~~The media cleaning cartridge of claim 16~~ For use in a printer or other system forming images on cards or other such media,

a replaceable media cleaning cartridge comprising:

a. a first cleaning component structured and arranged to engage and present to a moving media unit being cleaned, a changing first contact surface area; and

b. a second cleaning component structured and arranged to engage and present to said first cleaning component, a changing second contact surface area;

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

c. the tackiness of said second contact surface area being greater than the tackiness of said first contact surface areas which in turn is greater than the tackiness of a media unit such that said first contact surface area adhesively attracts particles from a media unit being cleaned, and said second contact surface area adhesively attracts particles from said first contact surface area.

wherein adapted to mount said first second cleaning component is mounted above said second first cleaning component such that gravity forces said first cleaning component against said media unit.

28. (currently amended) The media cleaning cartridge of claim 16 wherein the total second contact surface area on said second cleaning component is greater than the total first contact surface area on said first cleaning component.

29. (currently amended) The media cleaning cartridge of claim 16 wherein said second cleaning component comprises a disposable tube having said second surface area and a core upon which said tube is mounted.

30. (previously presented) The media cleaning cartridge of claim 29 wherein said core comprises a pair of end caps, one positioned in each end of said tube.

31. (currently amended) For use in a printer or other system forming images on cards or other such media, a replaceable media cleaning cartridge adapted to be received in the system and configured to support one or more cleaning components structured and arranged to engage and present to a moving media unit being cleaned a changing tacky contact surface area, wherein said cartridge comprises:

a. a first cleaning component structured and arranged to engage and present to the moving media unit being cleaned, a changing first contact surface area; and

b. a second cleaning component structured and arranged to engage and present to said first cleaning component, a changing second contact surface area.

wherein the tackiness of said second contact surface area is greater than the tackiness of said first contact surface areas.

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

32. (currently amended) ~~The media cleaning cartridge of claim 31 which is~~ For use in a printer or other system forming images on cards or other such media, a replaceable media cleaning cartridge adapted to be received in the system and configured to support one or more cleaning components structured and arranged to engage and present to a moving media unit being cleaned a changing tacky contact surface area, said cartridge is bidirectionally effective and adapted to receive a media unit on either of opposed first and second faces thereof.

33. (previously presented) The media cleaning cartridge of claim 31 including mounting structures adapted for quick installation of the cartridge in the system.

34. (currently amended) ~~The media cleaning cartridge of claim 33~~ For use in a printer or other system forming images on cards or other such media, a replaceable media cleaning cartridge adapted to be received in the system and configured to support one or more cleaning components structured and arranged to engage and present to a moving media unit being cleaned a changing tacky contact surface area, wherein said mounting structures include a latch.

35. (previously presented) ~~The media cleaning cartridge of claim 34~~ For use in a printer or other system forming images on cards or other such media, a replaceable media cleaning cartridge adapted to be received in the system and configured to support one or more cleaning components structured and arranged to engage and present to a moving media unit being cleaned a changing tacky contact surface area, including at least one upstanding tab adapted to be manually grasped for installation of the cartridge into the system.

36. (currently amended) ~~The media cleaning cartridge of claim 35~~ For use in a printer or other system forming images on cards or other such media, a replaceable media cleaning cartridge adapted to be received in the system and configured to support one or more cleaning components structured and arranged to engage and present to a moving media unit being cleaned a changing tacky contact surface area, wherein said cartridge includes an upstanding arm on each side of the cartridge.

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

37. (previously presented) The media cleaning cartridge of claim 36 wherein said arms are resilient and adapted to be flexed toward each other to facilitate installation of the cartridge in the system.

38. (currently amended) The media cleaning cartridge of claim 37 wherein said arms each have a detent provision configured to cooperate with detent provisions in the system to locate the cartridge in an operative position in the system.

39. (currently amended) ~~The media cleaning cartridge of claim 31~~ For use in a printer or other system forming images on cards or other such media, a replaceable media cleaning cartridge adapted to be received in the system and configured to support one or more cleaning components structured and arranged to engage and present to a moving media unit being cleaned a changing tacky contact surface area, including alignment members on opposed sides of the cartridge configured to be received in cooperating alignment guides in the system.

40. (previously presented) The media cleaning cartridge of claim 39 wherein said alignment members are structured to be received in slots in the system.

41. (currently amended) ~~The media cleaning cartridge of claim 31~~ For use in a printer or other system forming images on cards or other such media, a replaceable media cleaning cartridge adapted to be received in the system and configured to support one or more cleaning components structured and arranged to engage and present to a moving media unit being cleaned a changing tacky contact surface area, wherein said cartridge has a pivoted lid.

42. (previously presented) The media cleaning cartridge of claim 41 including a resilient member mounted to bias said lid to a closed position.

43. (currently amended) The media cleaning cartridge of claim 42 wherein said second cleaning component comprises a roller having an axle, and wherein said lid engages said axle to transfer said bias to said second cleaning component.



Appl. No.: 10/689,580  
Arndt. dated 10/27/2005  
Reply to Office action of June 27, 2005

44. (previously presented) The media cleaning cartridge of claim 31 wherein said cartridge has a frame which supports said one or more cleaning components and is configured to define a media access opening on a first face of said cartridge.

45. (previously presented) The media cleaning cartridge of claim 44 wherein said opening comprises a window with at least one beveled edge.

46. (previously presented) The media cleaning cartridge of claim 44 wherein said cartridge is adapted to receive a media unit to be cleaned through said opening along an input path having a predetermined acute entry angle relative to horizontal.

47. (previously presented) The media cleaning cartridge of claim 46 wherein said acute entry angle is about 15 degrees.

48. (currently amended) The media cleaning cartridge of claim 47, wherein said cartridge defines a media exit opening on a second face of said cartridge having an exit angle that is substantially horizontal.

49. (previously presented) The media cleaning cartridge of claim 46 wherein said cartridge is adapted to effect a media unit which has been cleaned through said opening along an output path having a predetermined exit angle which is different than said entry angle relative to horizontal.

50. (previously presented) A printer or other system forming images on cards or other such media, comprising:

- a. a chassis;
- b. a media feed supported by said chassis; and
- c. a replaceable media cleaning cartridge supported by said chassis adjacent the media feed, said cartridge comprising:
  - i. a first cleaning component structured and arranged to engage and present to a moving media unit being cleaned, a changing first contact surface area; and

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

- ii. a second cleaning component structured and arranged to engage and present to said first cleaning component, a changing second contact surface area;
- iii. the tackiness of said second contact surface area being greater than the tackiness of said first contact surface areas which in turn is greater than the tackiness of a media unit such that said first surface area adhesively attracts particles from a media unit being cleaned and said second surface area adhesively attracts particles from said first surface area.

51. (currently amended) The system of claim 50 wherein said first cleaning component comprises a roller.

52. (currently amended) The system of claim 50 wherein said second cleaning component comprises a roller.

53. (currently amended) The system of claim 50 wherein said second cleaning component is adapted for quick removal from said cartridge.

54. (previously presented) The system of claim 50 wherein said second surface is replaceable.

55. (currently amended) The system of claim 50 wherein said cartridge has a frame which supports said first and second cleaning components, said frame being configured such that at least said second cleaning component is supported in slots in said frame.

56. (currently amended) The system of claim 50 wherein said cartridge includes a resilient member for biasing said second cleaning component into engagement with said first cleaning component.

57. (currently amended) The system of claim 50 adapted to mount said first second cleaning component above said second first cleaning component such that gravity forces said first cleaning component against said media unit.

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

58. (previously presented) The system of claim 50 including mounting structures configured for quick installation in the system.

59. (previously presented) The system of claim 58 wherein said mounting structures include a latch.

60. (currently amended) The system of claim 50 wherein the total second contact surface area on said second cleaning component is greater than the total first contact surface area on said first cleaning component.

61. (currently amended) The system of claim 50 wherein said second cleaning component comprises a disposable tube having said second surface area and a core upon which said tube is mounted.

62. (currently amended) A printer or other system forming images on cards or other such media, comprising:

- a. a chassis;
- b. a media feed supported by said chassis; and
- c. a replaceable media cleaning cartridge supported by said chassis and adapted to

be received in the system, the cartridge being configured to support one or more cleaning components structured to engage and present to a moving media unit being cleaned a changing tacky contact surface area, wherein said cartridge comprises:

d. a first cleaning component structured and arranged to engage and present to the moving media unit being cleaned, a changing first contact surface area; and

e. a second cleaning component structured and arranged to engage and present to said first cleaning component, a changing second contact surface area

wherein the tackiness of said second contact surface area is greater than the tackiness of said first contact surface areas.

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

63. (previously presented) The system of claim 62 wherein said cartridge is bidirectionally effective to receive a media unit on either of opposed first and second faces thereof.

64. (previously presented) The system of claim 62 wherein said cartridge and said chassis have mounting structures adapted for quick installation of the cartridge in the system.

65. (previously presented) The system of claim 64 wherein said mounting structures include a latch.

66. (previously presented) The system of claim 62 wherein said cartridge includes at least one upstanding tab adapted to be manually grasped for installation of the cartridge into the system.

67. (previously presented) The system of claim 66 wherein said cartridge includes an upstanding arm on each side of the cartridge.

68. (previously presented) The system of claim 67 wherein said arm is resilient and adapted to be flexed to facilitate installation of the cartridge in the system.

69. (previously presented) The system of claim 68 wherein said arms have detent provisions configured to cooperate with detent provisions in the chassis to position the cartridge in the system.

70. (previously presented) The system of claim 62 including alignment members on opposed sides of the cartridge configured to be received in cooperating alignment guides in the chassis.

71. (previously presented) The system of claim 70 wherein said alignment guides comprise slots.

72. (previously presented) The system of claim 62 wherein said cartridge has a pivoted lid.

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

73. (previously presented) The system of claim 72 wherein said cartridge includes a spring mounted to bias said lid to a closed position.

74. (currently amended) The system of claim 73 wherein second cleaning component comprises a roller having an axle, and wherein said lid engages said axle to bias said second cleaning component against said first cleaning component.

75. (previously presented) The system of claim 62 wherein said cartridge has a frame configured to define a media access opening on a first face of said cartridge.

76. (previously presented) The system of claim 75 wherein said opening comprises a window with at least one beveled edge.

77. (previously presented) The system of claim 75 wherein said cartridge is adapted to receive a media unit to be cleaned through said opening along an input path having a predetermined acute entry angle relative to horizontal.

78. (previously presented) The system of claim 77 wherein said acute entry angle is about 15 degrees.

79. (currently amended) The system of claim 78, wherein said cartridge defines a media exit opening on a second face of said cartridge having an exit angle that is substantially horizontal.

80. (previously presented) The system of claim 77 wherein said cartridge is adapted to eject a media unit which has been cleaned through said opening along an output path having a predetermined exit angle which is different than said entry angle relative to horizontal.

81. (previously presented) A media cleaning method, comprising:
- a. providing a printer or other media image-forming system;
  - b. providing a cleaning cartridge for said system, comprising:

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

- i. a first cleaning component structured and arranged to engage and present to a moving media unit being cleaned a changing first contact surface area; and
- ii. a second cleaning component structured and arranged to engage and present to said first cleaning component a changing second contact surface area;
- iii. the tackiness of said second contact surface area being greater than the tackiness of said first contact surface areas which in turn is greater than the tackiness of a media unit such that said first surface area adhesively attracts particles from a media unit being cleaned and said second surface area adhesively attracts particles from said first surface area;
- iv. installing the cartridge in the system;
- c. moving media through said system until the effectiveness of said second cleaning component in cleaning media has diminished;
- d. withdrawing said cartridge from said system; and
- e. replacing said second cleaning component.

82. (currently amended) A printer or other system forming images on cards or other such media adapted for use with a replaceable media cleaning cartridge, the system comprising:

- a. a media feed; and
- b. a system chassis mounting the media feed and configured to receive and support a cartridge adjacent the feed such that a media unit being cleaned is transported by the feed in contact with the cartridge,
- c. the system chassis having spaced guides structured to guide and at least assist in retaining the cartridge on the system chassis,  
wherein said guides comprise slots.

83. (canceled).

84. (previously presented) The system of claim 82, wherein said guides are located on opposed walls of the system chassis.

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

85. (previously presented) The system of claim 84 wherein said guides comprise channels adapted to engage opposed sides of a cartridge and guide it into an operative position within the system.

86. (previously presented) The system of claim 85 wherein said channels are formed by projections from said opposed walls in said system chassis.

87. (previously presented) The system of claim 82 wherein said system chassis has at least one detent provision adapted to cause said cartridge to snap into said system chassis when the cartridge is located in its operative position.

88. (currently amended) A printer or other system forming images on cards or other such media having a snap-in media cleaning cartridge, comprising:

- a. a media cleaning cartridge configured to support one or more cleaning components and structured to engage and present to a moving media unit being cleaned a changing tacky contact surface area;
- b. a media feed; and
- c. a system chassis mounting the media feed and configured to receive and support the cartridge in an operative position adjacent the feed;
- d. the system chassis and the cartridge having cooperative cartridge retention provisions structured to cause said cartridge to snap into said operative position, wherein said cartridge has flexible arms on opposed sides which cooperate with channels or slots on opposed walls of said system chassis during installation of said cartridge in said system chassis.

89. (canceled).

90. (currently amended) The system of claim ~~88~~ 89 wherein said cartridge arms and said chassis channels or slots include a detent arrangement.

91. (previously presented) The system of claim 88 wherein said cartridge retention provisions include a detent.

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

92. (previously presented) The system of claim 88 wherein said cartridge retention provisions include one or more resilient members constituting part of the cartridge, and wherein said one or more resilient members are manually stressed during installation of the cartridge to contribute to the snap-in effect.

93. (previously presented) For use with a media cleaning cartridge for a printer or other system forming images on cards or other such media, the media cleaning cartridge having a first cleaning component structured to engage and present to a moving media unit being cleaned a changing first contact surface area, a second cleaning component comprising:

a. a changing second contact surface area configured and arranged to engage said first contact surface area of said first cleaning component,

b. the tackiness of said second contact surface area being greater than the tackiness of said first contact surface areas which in turn is greater than the tackiness of a media unit being cleaned such that said first surface area adhesively attracts particles from said media unit and said second surface area adhesively attracts particles from said first surface area,

c. said second cleaning component being structured to be readily removed from said cartridge and discarded when the tackiness of said second contact surface area is no longer capable of efficiently adhesively attracting particles from said first contact surface area on said first cleaning component.

94. (currently amended) The ~~he~~ second cleaning component of claim 93 comprising a tube having removable end caps.

95. (previously presented) The second cleaning component of claim 94 wherein said end caps have journals adapted to be received in open-ended slots in a cartridge frame.

96. (currently amended) The ~~he~~ second cleaning component of claim 93 configured as a roller.

97. (previously presented) A printer or other system forming images on cards or other such media, comprising:



Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

- a. a chassis;
- b. a media feed supported by said chassis; and
- c. a media cleaner supported by said chassis and positioned adjacent the media feed, said media cleaner comprising:
  - i. a first cleaning component structured and arranged to engage and present to a moving media unit being cleaned a changing first contact surface area; and
  - ii. a second cleaning component supported above said first cleaning component and resting under the force of gravity on said first cleaning component, said second cleaning component being structured and arranged to engage and present to said first cleaning component a changing second contact surface area;
  - iii. the tackiness of said second contact surface area being greater than the tackiness of said first contact surface areas which in turn is greater than the tackiness of a media unit such that said first surface area adhesively attracts particles from a media unit being cleaned and said second surface area adhesively attracts particles from said first surface area.

98. (currently amended) The system of claim 97 wherein said first cleaning component comprises a roller.

99. (currently amended) The system of claim 97 wherein said second cleaning component comprises a roller.

100. (currently amended) The system of claim 97 wherein said second cleaning component is structured for quick removal from the system.

101. (currently amended) The system of claim 97 wherein said second cleaning component is adapted to be disposable.

Appl. No.: 10/689,580  
Amdt. dated 10/27/2005  
Reply to Office action of June 27, 2005

102. (currently amended) The system of claim 97 wherein said cleaner has a frame which supports said first and second cleaning components, said frame being configured such that at least said second cleaning component is held in slots in said frame.

103. (currently amended) The system of claim 97 including a resilient member configured to bias said second cleaning component against said first cleaning component.

104. (currently amended) The media cleaner of claim 97 wherein the total second contact surface area on said second cleaning component is greater than the total first contact surface area on said first cleaning component.

105. (currently amended) The system of claim 97 wherein said second cleaning component comprises a disposable tube having externally said second surface area and a core upon which said tube is mounted.

106. (previously presented) The system of claim 105 wherein said core comprising a pair of end caps which fit into the ends of the tube.